


AXIS DEC

HEVC h.265 stand-alone 4K/UHD/HDR decoder



Key features:

- HEVC h.265 decoding
- 40ms low latency (all modes)
- Optional Quad-Sync mode: (quad-stream transport or wireless slo-mo mode)
- (1) ASI input
- Quad 3G HEVC mode, single 3G 1080p mode out
- (1) Genlock input (tri-level, bi-level, or black burst)
- Embedded, MPEG-1 layer 2, AAC-LC or HE-AAC 8 linear pair audio decoding
- RJ45 Ethernet connectivity with available IP streaming and web-GUI remote control
- 9 - 18 VDC power input
- 15W power consumption
- Compact, portable design (7.125" X 5.0" X 1.5")

• 4K UHD resolution:

- 3840X2160p, 4:2:2/4:2:0, 8/10-bit
60/59.94/50/30/29.97/25/24/23.98

• Supported 3G resolutions:

- 1920X1080p, 60/59.94/50 Hz
(via Level A or Level B dual link)

• Supported HD resolutions:

- 1920X1080i, 60/59.94/50 Hz
- 1920X1080p, 30/29.97/25/24/23.97 Hz
- 1920X1080psf, 30/29.97/25/24/23.97 Hz
- 1280X720p, 60/59.94/50 Hz

• Supported SD resolutions:

- 720X480i, 29.97 - 720X576i, 25 Hz

AXDEC HEVC Decoder



AXDEC Rear Panel

