AXRX-QDM

AXIS 2-way Diversity Receiver

WAVE CENTRAL

Quick-deploy COFDM receiver for portable applications.

Key features:

- Available in 2 or 5.8 GHz frequency bands
- -95dBm plus receiver sensitivity
- Ethernet GUI setup and control
- 6, 7, or 8 MHz DVB-T bandwidth
- QPSK, 16QAM, 64QAM DVB-T constellations
- 1/2, 2/3, 3/4, 5/6, and 7/8 DVB-T FEC
- 1/4, 1/8, 1/16, and 1/32 DVB-T guard interval
- AVC h.264 / MPEG-4 Part 10 compression
- 2 embedded audio pairs, 1 analog audio pair
- 9 - 16 VDC power input
- 20W power consumption
- Available with Anton Bauer or IDX battery mounts

- **Supported 3G resolutions:**
  - 1920X1080p, 60/59.94/50 Hz (via Level A or Level B dual link)
- **Supported HD resolutions:**
  - 1920X1080i, 60/59.94/50 Hz
  - 1920X1080p, 30/29.97/25/24/23.97 Hz
  - 1920X1080psf, 30/29.97/25/24/23.97 Hz
  - 1280X720p, 60/59.94/50 Hz
- **Supported SD resolutions:**
  - 720X480i, 59.94 - 720X576i, 50 Hz

- **Optional UHF input configuration**
  - (2) 150 - 850 MHz UHF inputs
  - Requires external block down converters (BDCs) not included

99 GARDEN PARKWAY, SUITE C, CARLISLE, PA 17013 | WAVECENTRALRF.COM | 1.888.736.9283